

MUELLER® BRAND SINGLE SECTION SERVICE OUTLET PIPE REPAIR CLAMPS



13

Rev. 1-06

501-509 Series Single Section Service Outlet Pipe Repair Clamps — for 2" through 12" cast iron, ductile iron, steel, A-C and PVC pipe.

Standard Lengths: 6", 7-1/2", 9", 10", 12", 15", 18", 20", 24", 30"

Nominal pipe size	Clamp size-number	Clamp O.D. range*				Cast Iron	Ductile Iron	Cast Iron O.D. PVC	Steel***	A-C Rough Barrel
		Inches		Millimeters						
		Min.	Max.	Min.	Max.					
2"	235	2.35	2.63	59.7	66.8	50-250,A,B,C,D	ALL	-	2"	-
2-1/2"	270	2.70	2.98	68.6	75.7	50-250,A,B,C,D	ALL	-	2-1/2"	-
3"	297	2.97	3.25	75.5	82.5	-	-	-	3" O.D.	-
3"	346	3.46	3.72	87.9	94.4	-	-	-	3"	-
3"	373	3.73	4.00	94.8	101.6	50-250,A,B,C,D	ALL	-	-	-
3-1/2"	396	3.96	4.25	100.6	107.9	-	-	-	3-1/2" (4"O.D.)	-
4"	445	4.45	4.87	113.1	123.6	50-250,A	ALL	CL.150,200	STD	-
4"	474	4.74	5.14	120.4	130.5	50-250,A,B,C,D	ALL	CL.150,200	-	CL.100**,150
4"	495	4.95	5.35	125.8	135.8	-	-	-	-	CL.100**,150
4"	520	5.20	5.60	132.1	142.2	-	-	-	-	CL.150,200
6"	566	5.66	5.91	143.7	150.1	-	-	-	-	-
6"	594	5.94	6.34	150.9	161.0	-	-	-	6" O.D.	-
6"	634	6.34	6.74	163.3	171.2	-	-	-	STD	-
6"	655	6.55	6.97	164.4	177.0	50-250,A	ALL	CL.150,200	STD	-
6"	684	6.84	7.24	173.8	183.8	50-250,A,B,C,D	ALL	CL.150,200	-	-
6"	704	7.04	7.44	178.9	188.9	-	-	-	-	CL.100**,150
6"	722	7.22	7.62	183.4	193.5	-	-	-	-	CL.200
8"	792	7.92	8.32	201.1	211.3	-	-	-	8" O.D.	-
8"	836	8.36	8.76	212.3	222.2	-	-	-	-	-
8"	853	8.53	8.93	216.7	226.8	-	-	-	STD	-
8"	899	8.99	9.39	228.4	238.5	50-250,A,B,C,D	ALL	CL.150,200	-	-
8"	925	9.25	9.65	235.0	245.1	-	-	-	-	CL.100**,150
8"	940	9.40	9.80	238.8	248.9	-	-	-	-	CL.200
10"	990	9.90	10.30	251.4	261.6	-	-	-	-	-
10"	1040	10.40	10.80	264.1	274.3	-	-	-	-	-
10"	1064	10.64	11.04	270.3	280.4	-	-	-	STD	-
10"	1104	11.04	11.46	280.5	291.0	50-250,A,B,C,D	ALL	CL.150,200	-	-
10"	1137	11.37	11.77	288.8	298.9	-	-	-	-	CL.100**
10"	1175	11.75	12.15	298.5	308.6	-	-	-	12" O.D.	CL.150,200
12"	1200	12.00	12.40	304.8	315.0	-	-	-	-	-
12"	1220	12.20	12.60	309.9	320.0	-	-	-	-	-
12"	1246	12.46	12.86	316.5	326.6	-	-	-	-	-
12"	1260	12.60	13.00	320.1	330.2	-	-	-	STD	-
12"	1314	13.14	13.56	333.8	344.4	50-250,A,B,C,D	ALL	CL.150,200	-	-
12"	1356	13.56	13.96	344.5	354.5	-	-	-	-	CL.100**
12"	1400	14.00	14.40	355.7	365.7	-	-	-	14"	CL.150,200

*Verify pipe O.D. before selecting clamp size.

**CAUTION—O.D. of class 100 A-C pipe varies greatly. Measure pipe O.D. to assure proper clamp selection.

***Also fits PVC Plastic Pipe - ASTM D2241 SDR 17 and lower and ASTM D1785 schedule 80 and above.