

T-28 DUCTILE IRON TAPPING SLEEVE



11

Rev. 8-10

- ❑ Catalog number--T-28 Dual Compression Seal Tapping Sleeve
- ❑ Sizes--range from 6"-16" main and outlet (see chart below for available size).
- ❑ Fits all classes of pipe through Class D pit cast gray iron.
- ❑ 3/8" test plug standard.
- ❑ Epoxy coated ductile iron construction.
- ❑ O-ring seals on outlet and flange connection.
- ❑ Outlet flange dimensions and drilling comply with ANSI B16.1, Class 125 and with MSS SP-60.
- ❑ Stainless steel bolts and nuts.
- ❑ 250 psig (1724 kPa) maximum working pressure.



T-28

Tapping Sleeve pipe information

Nominal size of main	O.D. Range of sleeve		Class and type of pipe
	Inch	mm	
4"	4.80 - 5.00	121.92 - 127.00	Fits all classes of pipe through Class D pit cast gray iron.
6"	6.90 - 7.10	175.26 - 180.34	
8"	9.05 - 9.03	229.87 - 236.22	
10"	11.10 - 11.40	281.94 - 289.56	
12"	13.20 - 13.50	335.28 - 342.90	
16"	17.40 - 17.80	441.96 - 452.12	

Sizes available

Nominal size of main	Outlet size				
	4"	6"	8"	10"	12"
4"	X	-	-	-	-
6"	X	X	-	-	-
8"	X	X	X	-	-
10"	X	X	X	X	-
12"	X	X	X	X	X
16"	X	X	X	X	X